

2001-11-19

# ELFA

## PRODUKTINFORMATION

Vi reserverar oss mot fel samt förbehåller oss rätten till ändringar utan föregående meddelande

**ELFA artikelnr**

**73-028-54 UTEC4018F ultraljud sänd/mo**

# 錫麟企業有限公司 Sencera Co. Ltd.

Tel:886-2-27046595 Fax:886-2-27041279 Email:justinel@ms14.hinet.net  
9F-5, No. 26, Sec. 3, Jen-Ai road, Taipei, 106, Taiwan, ROC. <http://welcome.to/sencera>

## AIR ULTRASONIC TRANSDUCERS

### ENCLOSED TYPE TRANSCEIVER

#### MODEL : UTEC4018F


#### 1. Features

- Anti-weather construction, with excellent humidity and temperature durability. Suitable for outdoor applications.
- High S.P.L. output : 105dB min.
- High sensitivity : -78 dB min.
- Uniform in quality

#### 2. Applications

- Parking meter
- Burglar alarm
- Level meter

#### 3. Dimensions



#### 4. Ratings

Nominal Frequency (KHz)	40±1
Sensitivity (dB)	-75 min.
Sound Pressure Level (dB)	105 min.
Bandwidth (KHz)	1.5 min.
Capacitance (pf)	1700±25%
Maximum Input Voltage(Vrms)	20


# 錫麟企業有限公司 Sencera Co. Ltd.

Tel:886-2-27046595 Fax:886-2-27041279 Email:justinel@ms14.hinet.net


9F-5, No. 26, Sec. 3, Jen-Ai road, Taipei, 106, Taiwan, ROC. <http://welcome.to/sencera>

## 5. Test Circuits Diagram

### a) Test Circuit Diagram for Receiving



### b) Test Circuit Diagram for Transmitting



## 6. Environmental Characteristics

Item	Conditions	Variation of Sensitivity
Temperature Characteristics	-20~60°C	Within 10 dB
Humidity	40±2°C, 90-95 %RH, 100Hrs	Within 3 dB
Shock	50G impact Directions : 3 perpendicular directions Times : 3 times	Within 3 dB
Vibration	Directions : 3 perpendicular directions Times : 3 hours Single harmonic vibration a) Amplitude: 1.5mm Sweep Frequency : 10-50-10Hz with interval of 1 minute	Within 3 dB

# Sencera Co. Ltd.


# Data Sheet

Tel: 886-2-27046595

Fax: 886-2-27041279

justinc@msl4.hinet.net

http://welcome.to/sencera



UTECA018F reference circuit