

GoRugged R3000 Quad

Industrial Cellular VPN Router with 4 Ethernet Ports

for GPRS/EDGE/UMTS/HSPA/EVDO/4G LTE Networks

Robustel GoRugged R3000 Quad is a rugged cellular router offering state-of-the-art mobile connectivity for machine to machine (M2M) applications.

Key Features

- Dual SIM redundancy for continuous cellular connections, supports 2G/3G/4G.
- 4 Ethernet ports for layer 2 switch
- WAN link management: cellular WAN/Ethernet WAN/WLAN WAN backup.
- VPN tunnel: IPSec/OpenVPN/PPTP/L2TP/GRE.
- Supports Modbus gateway (Modbus RTU/ASCII to Modbus TCP).
- Supports GPS (optional), provides real time location and tracking.
- Supports 802.11 b/g/n Wi-Fi (optional), AP and client mode.
- Supports SDK, provides user programmatic interface.
- Supports 802.1Q VLAN tagging.
- Supports IP Pass-through.
- Auto reboot via SMS/Caller ID/Timing.
- Supports RobustLink (Centralized M2M management platform).
- Flexible Management methods: Web/CLI/SNMP/RobustLink.
- Firmware upgrade via Web/CLI/USB/SMS/RobustLink.
- Various interfaces: RS232/RS485/Console/USB/Ethernet.
- Wide range input voltages from 9 to 60 VDC and extreme operating temperature.
- The metal enclosure can be mounted on a DIN-rail or on the



Applications

- ATM/Vending Machine Connectivity
- Solar/Wind Energy Monitor
- Distribution Automation
- Automatic Meter Reading
- Industrial Automation
- IP Video Surveillance
- Remote Devices

Selection and Ordering Data

Model No.	Description	Operating Environment
R3000-Q2GA	GPRS Router, 4 Ethernet ports, 1 RS232 port	-40 to 85°C/5 to 95% RH
R3000-Q2GB	GPRS Router, 4 Ethernet ports, 1 RS485 port	-40 to 85°C/5 to 95% RH
R3000-Q3PA	HSPA+ Router, 4 Ethernet ports, 1 RS232 port	-40 to 85°C/5 to 95% RH
R3000-Q3PB	HSPA+ Router, 4 Ethernet ports, 1 RS485 port	-40 to 85°C/5 to 95% RH
R3000-Q3EA	EVDO Rev A/B Router, 4 Ethernet ports, 1 RS232 port	-20 to 60°C/5 to 95% RH
R3000-Q3EB	EVDO Rev A/B, 4 Ethernet ports, 1 RS485 port	-20 to 60°C/5 to 95% RH
R3000-Q4LA	FDD LTE Router, 4 Ethernet ports, 1 RS232 port	-25 to 60°C/5 to 95% RH
R3000-Q4LB	FDD LTE, 4 Ethernet ports, 1 RS485 port	-25 to 60°C/5 to 95% RH

GoRugged R3000 Quad

Industrial Cellular VPN Router with 4 Ethernet Ports

Specifications

Cellular Interface

- Standards: GSM/GPRS/EDGE/UMTS/HSPA+/EVDO/FDD LTE
- GPRS/EDGE: 850/900/1800/1900 MHz
- HSPA+: 850/900/1900/2100 MHz, DL/UL 21/5.76 Mbps, fallback to 2G
- FDD LTE: 800/900/1800/2100/2600 MHz, DL/UL 100/50 Mbps, fallback to 3G/2G
- EVDO: 450 or 800/1900 MHz, Rev A/B
- SIM: 2 x (3V & 1.8V)
- Antenna Interface: SMA Female

Ethernet Interface

- Number of Ports: 4 x 10/100 Mbps, 4 LANs or 3 LAN 1 WAN
- Magnet Isolation Protection: 1.5KV

WLAN Interface (Optional)

- Standards: 802.11b/g/n up to 65 Mbps, AP and Client mode
- Frequency Band: 2.400 - 2.500 GHz (2.4 GHz ISM band)
- Security: Open ,WPA, WPA2
- Encryption: AES, TKIP
- Antenna Interface: SMA Female
- Transmission Power: 802.11b: 17dBm, 802.11g/n: 15dBm
- Reception Sensibility: 1M: -97dBm, 2M: -93dBm, 6M: -91dBm, 11M: -89dBm, 54M: -75dBm, 65M: -72dBm

GPS Interface (Optional)

- Antenna Interface: SMA Female, 50 ohms impedance
- Tracking Sensitivity: better than -158 dBm
- Protocol: NMEA-0183 V2.3

Serial Interface

- Number of Ports: 1 x RS-232 or 1 x RS-485
- ESD Protection: $\pm 15KV$
- Parameters: 8E1, 8O1, 8N1, 8N2, 7E2, 7O2, 7N2, 7E1
- Baud Rate: 300bps to 230400bps
- RS-232: Tx/D, Rx/D, RTS, CTS, GND
- RS-485: Data+ (A), Data- (B), GND
- Interface: 3.5mm terminal block with lock

System

- LED Indicators: RUN, PPP/WLAN, USR, RSSI, NET, SIM
- Built-in RTC, Watchdog, Timer
- Expansion: 1 x USB 2.0 host up to 480 Mbps
- Storage: 1 x MicroSD

Software

- Network protocols: PPP, PPPoE, TCP, UDP, DHCP, ICMP, NAT, DMZ, RIP v1/v2, OSPF, DDNS, VRRP, HTTP, HTTPS, DNS, ARP, QoS, SNTP, Telnet, VLAN, etc
- VPN tunnel: IPSec/OpenVPN/PPTP/L2TP/GRE
- Firewall: SPI, anti-DoS, Filter, Access Control
- Management: Web, CLI, SNMP v1/v2/v3, SMS, RobustLink
- Serial Port: TCP client/server, UDP, Modbus RTU/ASCII to Modbus TCP, Virtual COM (COM port redirector)
- RobustLink: Centralized M2M management platform

Power Supply and Consumption

- Power Supply Interface: 5mm terminal block with lock
- Input Voltage: 9 to 60 VDC
- Power Consumption: Idle: 100 mA @ 12 V
Data Link: 400 mA (peak) @ 12 V

Physical Characteristics

- Housing & Weight: Metal, 500g
- Dimension: (L x W x H): 125 x 108 x 45 mm
- Installation: 35mm Din-Rail or wall mounting or desktop

Regulatory and Type Approvals

- Approval & Detective: CE, R&TTE, FCC, RCM, RoHS, WEEE
- EMC: EN 61000-4-2 (ESD) Level 4, EN 61000-4-3 (RS) Level 4
EN 61000-4-4 (EFT) Level 4, EN 61000-4-5 (Surge) Level 3
EN 61000-4-6 (CS) Level 4, EN 61000-4-8, EN 61000-4-12

Packing List

- Robustel R3000 Quad Router
- Terminal Block for Power, I/O and Serial Port
- Document and Software CD

Optional Accessories (can be purchased separately)

- AC/DC Power Supply Adapter
- Rubber SMA Antenna
- 35mm Din-Rail mounting kit or Wall mounting kit
- Diversity antenna for HSPA+/LTE/EVDO

Contact:

www.robustel.com

info@robustel.com